

DRY LUBE SPRAY (GRAPHITE)

MAINTENANCE,
REPAIRS &
OPERATIONS
SOLUTION



TECHNICAL DATA SHEET

DESCRIPTION :

Aerolub dry lube spray dry (Graphite) a combination of specially processed micro fine graphite solid film lubricant and special anti-wear additives. On spraying, it deposits a thin film that air dries quickly without requiring any baking or heating. It bonds onto metal surfaces to form a coating to protect the surface from wear and friction and provides lubrication under hostile operating conditions of temperatures and high loadings. It has very good resistance to water and chemicals and is electrically conductive.

APPLICATIONS :

Pre-assembly & Thread Lubricant (anti-seize), Gaskets, Chains, Locks, Plant Machinery & Handling Equipment, Hoists & Winches, Rollers, Bearings & Bushings, Gears, Sprocket, Conveyors.

PROPERTIES:

Appearance	Greyish Black Color
Specific gravity	<1.00g/cc
NVM%	20±02%
Flammability	Flammable
Upper Temperature limit	500°C
Water Resistivity	Very Good
Flash Point	-18°C
Viscosity@25°C	N/A
Propellant	Propane,Butane
Solubility	Insoluble in Water

BENEFITS :

- Lowers friction, prevents galling and seizure.
- Does not attract dust and resists dirt buildup.
- Provides oil free lubrication to sliding components.
- Withstands high temperatures up to +500°C.
- Prevents metal-to-metal contact and reduces wear and tear of machinery.
- Quick bonding, air-drying and does not require any special treatment.
- Does not dislodge or blow away under high loads and pressures.
- Withstands corrosive and hostile environments.
- Does not contain any ozone depleting substances, CFC's or harmful chlorinated solvents.

Available Packaging : 100ml, 250ml, 400ml aerosol spray.

Shelf Life : 24 months from date of manufacture in sealed condition.

DRY LUBE SPRAY (GRAPHITE)

MAINTENANCE,
REPAIRS &
OPERATIONS
SOLUTION



TECHNICAL DATA SHEET

HOW TO USE :

- Never use on energized equipment or hot surfaces.
- Before spraying, shake can well until the marble noise from inside the container is clearly audible.
- Hold can 12 to 14 inches from surface to be coated, and press spray head firmly and spray a thin film.
- Leave for 1min to dry.

Caution : Contents under pressure. Do not puncture, pierce, or incinerate the container, even after use. Protect from sunlight and store away from heat and sources of ignition. Do not use it on energized equipment or on live circuits. Do not expose to temperatures exceeding 50°C (120°F). Use only in well-ventilated areas. As this can conduct electricity, prevent the risk of electrical shock by keeping away from all live electrical connections and sources of electricity. Do not breathe vapors or spray mist. Harmful by inhalation and avoid contact with skin and eyes. In case of eye contact, flush your eyes with water and contact a physician. If swallowed, may be harmful or fatal. DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. KEEP OUT OF REACH OF CHILDREN.

General : Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, and short and long-term exposure, refer to this product's safety data sheet (SDS). Dispose as industrial waste only in accordance with governing regulations. For proper disposal, empty aerosol can be completely.

Handling : Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safety, short and long-term exposure, and physical and health hazards and is available from Aerolub or your local Aerolub distributor or contact care@aerolubspecialties.com.

Limited Warranty : The information and data contained in this sheet are accurate to the best of our knowledge or are obtained from sources, tests, or experiences believed by us to be reliable and accurate. User ® is responsible for determining whether the recommended Aerolub product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data is offered without warranty.

AEROLUB SPECIALTIES INDIA PVT. LTD.

Works : Plot no. 3543-1, Phase - 4, GIDC,
Chhatral - 382729, Gujarat, India.

Email : aerolubspecialties@gmail.com

Website : www.aerolubspecialties.com

Disclaimer : ©2023 Aerolub

"Aerolub" is intended and authorized for use only in countries and jurisdiction in which Aerolub Specialties India Pvt. Ltd. is under Trademark registration for the rights to use, market and advertise the brand. Aerolub shall not be liable to third parties for unauthorized use of this document unauthorized use of trademarks. Contact for more information or mail to aerolubspecialties@gmail.com