

PAINT & GASKET REMOVER

CLEANERS
AND
DEGREASERS



TECHNICAL DATA SHEET

DESCRIPTION :

Aerolub Paint and Gasket Remover Paint & Gasket Remover is a fast-acting blend of solvents for removal of paints, gaskets, adhesives, sealants, lacquers and varnishes without excessive scraping or causing damage to the surfaces. It also cleans stubborn grease, oil, varnish and carbon deposits.

APPLICATIONS :

For removal of baked-on gaskets, gasket cements and formed-in place types of gaskets, removal of paint, adhesives, lacquers and varnishes without excessive scraping or causing damage to the surfaces. For cleaning stubborn grease, oil, varnish, carbon deposits.

PROPERTIES:

Appearance	Clear Colorless
Specific gravity	1.18±0.02g/cc
NVM%	2.00±02
Flammability	Flammable
Kinematic viscosity @ 20°C	N/A
Propellant	Propane, Butane
Solubility	Insoluble in Water
Dielectric Strength	37500volt (ASTM D 877)
Kauri Butanol Value (KB)	93(ASTM D 1130)

BENEFITS :

- Removes gaskets, paints, sealants, varnishes.
- Fast acting formula cleans dried grease & oil Protects surface finish from excessive scraping.
- Quickly dislodges oil, grease, silicones, fingerprints, carbon, oxides and other light contaminants.
- Extends wear life of the equipment and reliability of performance.

Available Packaging : 100ml, 250ml, 400ml Aerosol Spray.

Shelf Life : 24 months from date of manufacture in sealed condition.

PAINT & GASKET REMOVER

CLEANERS
AND
DEGREASERS



TECHNICAL DATA SHEET

HOW TO USE :

- Observe precautions of wearing protective eyewear and hand gloves while handling this product.
- Spray liberally over surface and allow solvents 5-10 minutes to work for softening paint and then remove with a putty knife or cloth rag.
- For stubborn or thick coatings, repeat the same procedure.
- To prevent clogging of actuator and valve dip tube after use, invert the can and press the actuator button for a short burst till only clear propellant gas comes out.
- Not safe around sensitive plastics.

Caution : Contents under pressure. Do not puncture, pierce, or incinerate the container, even after use. Protect from sunlight and store away from heat and sources of ignition. Do not use it on energized equipment or on live circuits. Do not expose to temperatures exceeding 50°C (120°F). Use only in well-ventilated areas. As this can conduct electricity, prevent the risk of electrical shock by keeping away from all live electrical connections and sources of electricity. Do not breathe vapors or spray mist. Harmful by inhalation and avoid contact with skin and eyes. In case of eye contact, flush your eyes with water and contact a physician. If swallowed, may be harmful or fatal. DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. KEEP OUT OF REACH OF CHILDREN.

General : Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, and short and long-term exposure, refer to this product's safety data sheet (SDS). Dispose as industrial waste only in accordance with governing regulations. For proper disposal, empty aerosol can be completely.

Handling : Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safety, short and long-term exposure, and physical and health hazards and is available from Aerolub or your local Aerolub distributor or contact care@aerolubspecialties.com.

Limited Warranty : The information and data contained in this sheet are accurate to the best of our knowledge or are obtained from sources, tests, or experiences believed by us to be reliable and accurate. User ® is responsible for determining whether the recommended Aerolub product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data is offered without warranty.

AEROLUB SPECIALTIES INDIA PVT. LTD.

Works : Plot no. 3543-1, Phase - 4, GIDC,
Chhatral - 382729, Gujarat, India.

Email : aerolubspecialties@gmail.com

Website : www.aerolubspecialties.com

Disclaimer : ©2023 Aerolub

"Aerolub" is intended and authorized for use only in countries and jurisdiction in which Aerolub Specialties India Pvt. Ltd. is under Trademark registration for the rights to use, market and advertise the brand. Aerolub shall not be liable to third parties for unauthorized use of this document unauthorized use of trademarks. Contact for more information or mail to aerolubspecialties@gmail.com