

DESCRIPTION :

Aerolub Penlub Fast Acting Spray oil loosens rust and corrosion formed by alkali, fruit acids, water, and electrolytes. Low surface tension allows the oil to migrate into tight spaces and along threaded fasteners. Reduces the tugging and pounding sometimes required to loosen screws and bolts. Loosens tar, dirt, and carbon on stubborn, rusted bolts.

APPLICATIONS :

Aerolub Penlub Pro quick release for nuts, bolts, pipes, fittings, pumps, pulleys, battery cables, roller conveyers, hinges and valves. Use on metals, alloys, rubber, and most painted surfaces.

PROPERTIES:

Appearance	Pale Yellow Color
Specific gravity	0.80±0.02 g/cc
NVM%	N/A
Flammability	Flammable
Penetrating Ability	Excellent
Corrosion Protection	Very Good
Flash Point	60°C
Viscosity@25°C	7-9 cps@60rpm, S2
Propellant	Propane,Butane
Solubility	Insoluble in Water

BENEFITS :

- Displaces moisture and eliminates damp induced faults.
- Rapidly penetrates and releases seized parts.
- Cleans surfaces effectively, removing greases, heavy oils, waxes and more.
- 360° Valve allows product to be sprayed in any position even inverted.
- Contains no acid and is effective against salt water corrosion.

Available Packaging : 100ml, 250ml, 400ml aerosol spray.

Shelf Life : 24 months from date of manufacture in sealed condition.

HOW TO USE :

- Never use on energized equipment or hot surfaces.
- Before spraying, shake can well.
- Hold can 12 to 14 inches from surface to be coated, and press spray head firmly. Use steady, even strokes while spraying, making sure to keep spraying hand in motion.
- Leave for 10-20min to allow liquid to penetrate and free rusted parts.
- Period for penetration may vary depending upon the length of time the product has been rusted for and in some cases may even take up to hours. Use an absorbent rag or a brush to remove dirt, rust, scales & dust.

Caution : Contents under pressure. Do not puncture, pierce, or incinerate the container, even after use. Protect from sunlight and store away from heat and sources of ignition. Do not use it on energized equipment or on live circuits. Do not expose to temperatures exceeding 50°C (120°F). Use only in well-ventilated areas. As this can conduct electricity, prevent the risk of electrical shock by keeping away from all live electrical connections and sources of electricity. Do not breathe vapors or spray mist. Harmful by inhalation and avoid contact with skin and eyes. In case of eye contact, flush your eyes with water and contact a physician. If swallowed, may be harmful or fatal. DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. KEEP OUT OF REACH OF CHILDREN.

General : Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, and short and long-term exposure, refer to this product's safety data sheet (SDS). Dispose as industrial waste only in accordance with governing regulations. For proper disposal, empty aerosol can be completely.

Handling : Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safety, short and long-term exposure, and physical and health hazards and is available from Aerolub or your local Aerolub distributor or contact care@aerolubspecialities.com.

Limited Warranty : The information and data contained in this sheet are accurate to the best of our knowledge or are obtained from sources, tests, or experiences believed by us to be reliable and accurate. User ® is responsible for determining whether the recommended Aerolub product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data is offered without warranty.

AEROLUB SPECIALITIES INDIA PVT. LTD.

Works : Plot no. 3543-1, Phase - 4, GIDC,
Chhatral - 382729, Gujarat, India.

Email : aerolubspecialities@gmail.com

Website : www.aerolubspecialities.com

Disclaimer : ©2023 Aerolub

"Aerolub" is intended and authorized for use only in countries and jurisdiction in which Aerolub Specialities India Pvt. Ltd. is under Trademark registration for the rights to use, market and advertise the brand. Aerolub shall not be liable to third parties for unauthorized use of this document unauthorized use of trademarks. Contact for more information or mail to aerolubspecialities@gmail.com