

# CITRUS CLEANER (FOR METAL)

CLEANERS  
AND  
DEGREASERS



TECHNICAL DATA SHEET

## DESCRIPTION :

**Aerolub Citrus Cleaner** is a heavy-duty cleaner / degreaser which rapidly penetrates through grease, oil, dirt, dust and other contaminants and cleans equipment fast. It is a naturally formed, readily biodegradable cleaner having a pleasant citrus odor and does not leave any residue. Aerolub Citrus Cleaner is ideal for tough cleaning jobs for removal of stubborn contaminants as tar, adhesives, bitumen and other such soils where regular grade cleaning agents fail. It does not contain any CFC's, chlorinated solvents or ozone depleting chemicals and is suitable for cleaning / degreasing of all metal surfaces and equipment only.

## APPLICATIONS :

For heavy duty cleaning / degreasing applications of all mechanical and electromechanical equipment as chains, wire ropes, steel cables, dies, molds, automotive parts, motors, bearings, generators, gears, compressors, portable tools.

## PROPERTIES:

Appearance	Clear Colorless
Specific gravity	0.78±0.02g/cc
Flammability	Flammable
Kinematic viscosity @ 20°C:	N/A
Propellant	CO <sub>2</sub>
Solubility	Insoluble in Water

## BENEFITS :

- Removes grease, oil, dirt, dust, sludge.
- Non corrosive, nonconductive & non staining.
- Removes tar, adhesives and other tough contaminants.
- Leaves no residue.
- Safe on metals, most plastics, glass and ceramics.
- Non chlorinated formulation.
- Fast penetrating and superior wetting action.
- 360° valve allows spraying in any position—even inverted

**Available Packaging :** 100ml, 250ml, 400ml Aerosol Spray.

**Shelf Life :** 24 months from date of manufacture in sealed condition.

# CITRUS CLEANER (FOR METAL)

CLEANERS  
AND  
DEGREASERS



TECHNICAL DATA SHEET

## HOW TO USE :

- Never use on energized equipment.
- Spray using pin-point extension tube onto soiled surface and continue spraying liberally until only solvent runs out clearly and contaminants have been washed off.
- To remove heavy carbon or oxides, use a brush. Spray starting at the top of the surface and slowly working towards the bottom.
- Allow solvents to dry off the components before reactivating.
- To enhance drying time, apply forced air or wipe dry with an absorbent cloth after applying.
- Use only when completely dry.
- Test on plastics prior to use for compatibility.

**Caution :** Contains flammable solvents. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

**Caution :** Contents under pressure. Do not puncture, pierce, or incinerate the container, even after use. Protect from sunlight and store away from heat and sources of ignition. Do not use it on energized equipment or on live circuits. Do not expose to temperatures exceeding 50°C (120°F). Use only in well-ventilated areas. As this can conduct electricity, prevent the risk of electrical shock by keeping away from all live electrical connections and sources of electricity. Do not breathe vapors or spray mist. Harmful by inhalation and avoid contact with skin and eyes. In case of eye contact, flush your eyes with water and contact a physician. If swallowed, may be harmful or fatal. DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. KEEP OUT OF REACH OF CHILDREN.

**General :** Use in well-ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, and short and long-term exposure, refer to this product's safety data sheet (SDS). Dispose as industrial waste only in accordance with governing regulations. For proper disposal, empty aerosol can be completely.

**Handling :** Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safety, short and long-term exposure, and physical and health hazards and is available from Aerolub or your local Aerolub distributor or contact [care@aerolubspecialties.com](mailto:care@aerolubspecialties.com).

**Limited Warranty :** The information and data contained in this sheet are accurate to the best of our knowledge or are obtained from sources, tests, or experiences believed by us to be reliable and accurate. User ® is responsible for determining whether the recommended Aerolub product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data is offered without warranty.

## AEROLUB SPECIALTIES INDIA PVT. LTD.

**Works :** Plot no. 3543-1, Phase - 4, GIDC,  
Chhatral - 382729, Gujarat, India.

**Email :** [aerolubspecialties@gmail.com](mailto:aerolubspecialties@gmail.com)

**Website :** [www.aerolubspecialties.com](http://www.aerolubspecialties.com)

**Disclaimer :** ©2023 Aerolub

"Aerolub" is intended and authorized for use only in countries and jurisdiction in which Aerolub Specialties India Pvt. Ltd. is under Trademark registration for the rights to use, market and advertise the brand. Aerolub shall not be liable to third parties for unauthorized use of this document unauthorized use of trademarks. Contact for more information or mail to [aerolubspecialties@gmail.com](mailto:aerolubspecialties@gmail.com)